WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2132
Rec. Jan 23 1953
Well No. 1
Permit No.
Do not fill in

Owner Mr Martin S. Hanson Driller John Frewalt
Address 210 Tonopah Hwy Las Vegas Nev. Address Gen Del Whole Las Vegas Lic. No. 9
Location of well N½ SW¼ NE¼ NW¼ Sec. 6, T. 21 S/N, R. 59 E, in Clark County
or
Water will be used for Domestic Total depth of well 160 FT.
Size of drilled hole 8" Weight of casing per linear foot 24 lb
Thickness of casing 1/4 in Temp. of water
Diameter and length of casing 8" I.D. 33 FT LONG
(Casing 10" in diameter and under give inside diameter; casing 10" in diameter give outside diameter)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 63 FT. 6 in.
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well NOV. 21 52 Date of completion of well JAN. 19th 1953
Type of well rig STAR

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
		148 FT	HARD BAKED CLAY
48	50	2 FT	TALC
50	56	6 FT	BROKEN UP LIME WATER RISING 96.6

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 48 to 56 ft.
Other aquifers TALC - 2 FT BROKEN UP LIME

First water at 48 feet.

Casing perforated
from to ft.

Size of perforations

(OVER)

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
81.D			33 FT	CASING DRIVEN INTO CLAY ABOUT A HALF YARD of GROUT

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Jack Fremont
Well Driller

By

License No. 9

Dated JAN 17 53, 19 53

(Not to be filled in by Driller)