

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA



Log No. 2147  
Rec. Feb. 13 1953  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_

Owner BORDA LAND-SHEEP Driller HARVEY MEYER  
Address DATTON, RANCH. Address CARSON CITY Lic. No. 10  
Location of well: 1/4 1/4 Sec. 5, T. 16N, R. 22E, in LYON County  
or \_\_\_\_\_  
Water will be used for Stock Total depth of well 55' 6"  
Size of drilled hole 6" Weight of casing per linear foot 20 lbs.  
Thickness of casing 5/16 Temp. of water WARM  
Diameter and length of casing 6" 55' 6"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
If flowing well give flow in c.f.s. or g.p.m. and pressure no  
If nonflowing well give depth of standing water from surface 6'  
If flowing well describe control works no (Type and size of valve, etc.)  
Date of commencement of well JAN 8 1953 Date of completion of well JAN 9 1953  
Type of well rig \_\_\_\_\_

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	DARK CHAY.
4	12	8	SANDY CLAY.
12	20	8	SAND WATER.
20	26	6	SANDY BLUE CLAY.
26	55 1/2	29	SAND WATER.

Water-bearing Formation, Casing Perforations, Etc.  
Chief aquifer (water-bearing formation)  
from 26 to 55 ft.  
Other aquifers \_\_\_\_\_  
First water at 12 feet.  
Casing perforated from 0 to 17 ft.  
Size of perforations 1/8

