

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2180  
 Rec. Mar 11 1953  
 Well No. \_\_\_\_\_  
 Permit No. 14573  
*Do not fill in*

Owner Chauncy Florey Driller J. B. Reynolds  
 Address Mine Address Fallon Lic. No. 29  
 Location of well: SW 1/4 SE 1/4 Sec. 8, T. 6 N/8, R. 35 E, in Mineral County  
 or S.E. corner town  
 Water will be used for Industrial Total depth of well 303  
 Size of drilled hole 8 & 6 Weight of casing per linear foot std.  
 Thickness of casing std. pipe Temp. of water Cold  
 Diameter and length of casing 8" X 190' & 6" X 303'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 120'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Jan 5 53 Date of completion of well Jan 17  
 Type of well rig Percussion

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	122	122	Surface wash, clay & gravel
122	124	2	Sand & gravel
124	188	64	hard conglomerate
188	240	52	Clay & gravel
240	250	10	coarse water gravel
250	270	20	clay & small rocks
270	284	14	loose gravel & sand
284	303	19	ssand & gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 240 to 250 ft.

Other aquifers \_\_\_\_\_

122 - 124

270 - 303

First water at 122 feet.

Casing perforated

from 120 to 303 ft.

Size of perforations

3/8 X 5"

