

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA



Log No. 2187  
Rec. MARCH 30 1953  
Well No.  
Permit No.

Do not fill in

Owner NEVADA ORE REFINING CORP. Office HARVEY MEYER.  
Address RENO HOT SPRINGS Address CARSON CITY Lic. No. 10  
Location of well: SW 1/4 SE 1/4 Sec. 29, T. 18 N/S, R. 20 E, in WASHOE County  
or  
Water will be used for REFINING Total depth of well 295'  
Size of drilled hole 6" Weight of casing per linear foot 20 LBS.  
Thickness of casing 5/16 Temp. of water HOT.  
Diameter and length of casing 6" - 20'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
If flowing well give flow in c.f.s. or g.p.m. and pressure 20 GAL - 18 LBS.  
If nonflowing well give depth of standing water from surface 39'  
If flowing well describe control works MASTER SPATE.  
(Type and size of valve, etc.)  
Date of commencement of well JAN 10 Date of completion of well FEB 26th  
Type of well rig CABLE TOOLS.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	23	23	BROKENHIME QUARTZ
23	58	35	DYRITE DARK.
58	60	2	LITTLE WATER STRAIN
60	105	40	DYRITE DARK.
105	175	70	DYRITE GRAY.
175	189	14	CLAY GRAY.
189	220	81	DYRITE GRAY.
220	295	25	DYRITE DARK.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 175 to 295 ft.

Other aquifers

First water at 58 feet.

Casing perforated

from 70 to 70 ft.

Size of perforations

70

