WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2207
Rec. ..... 19.....
Well No. .....
Permit No. 11600
Do not fill in

copy to cc.

Owner Murray Wollman Driller J.A. Ezzinger
Address Boulder City Hwy. Address Las Vegas Nev Lic. No. 63
Location of well: SE ¼ SE ¼ Sec. 1, T. 21 N/S, R. 61 E, in Clark County
or.....

Water will be used for Domestic Total depth of well 520
Size of drilled hole 8 in Weight of casing per linear foot 26 lb
Thickness of casing 5/16 in Temp. of water 73°
Diameter and length of casing 8 in I.D. 100' 2"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure 30 to 35 gals. per minute
If nonflowing well give depth of standing water from surface.....
If flowing well describe control works + 22.4 3/19/53
(Type and size of valve, etc.)
Date of commencement of well 2/3/53 Date of completion of well 2/16/53
Type of well rig "71 Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	gravel
10	22	12	yellow sdy clay
22	25	3	sand (water)
25	31	6	red sdy clay
31	34	3	yellow sdy clay
34	36	2	lime rock
36	42	6	white clay
42	44	2	gravel
44	48	4	yellow clay
48	50	2	sand rock
50	57	7	white sdy clay
57	60	3	lime rock
60	69	9	yellow clay
69	81	12	gravel
81	97	16	yellow clay
97	103	6	red clay
103	107	4	gravel & sand
107	123	16	yellow clay
123	146	23	red sdy clay
146	187	43	yellow sdy clay
187	205	16	red sand (water)
205	330	125	red sticky clay
330	385	55	yellow clay
385	405	20	red sticky clay
405	409	5	blue clay & gravel

(over)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 22 to 25 ft.
Other aquifers 189-205
491-494
494-485
495-520

First water at 25 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
409	416	7	Brown clay
416	466	50	Red clay
466	471	5	yellow clay
471	474	3	Brown sand (water)
474	485	11	Gravel (water)
485	489	4	yellow clay
489	495	6	Brown sticky clay
495	520	25	Brown sand & Gravel (water)

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D	0	100' 2"		cemented 0 to 98'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Bert Harrison
Well Driller

By

License No. 63

Dated 4/17, 1953

(Not to be filled in by Driller)