

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2208
 Rec. April 16 1953
 Well No. _____
 Permit No. _____

Do not fill in

Owner Orovada School Driller A.E. Hosack & Son

Address Orovada, Nevada Address Nampa, Idaho Lic. No. 62

Location of well: NW 1/4 NW 1/4 Sec. 35, T. 43 N, R. 37 E, in Humboldt County
 or 250' E from NW corner and 150' S from NW cor. of NW 1/4, 35/43/37

Water will be used for domestic Total depth of well 122'

Size of drilled hole 6" & 4" Weight of casing per linear foot 6" - 19#, 4" - 10#

Thickness of casing 6" - .280", 4" - .237" Temp. of water _____

Diameter and length of casing 107'-10" of 6" I.D. & 21'-4" of 4" I.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 65'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Nov. 12, 1952 Date of completion of well Nov. 25, 1952

Type of well rig 71 Star with cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Soil
12	60	48	Cemented gravel
60	110	50	Gray clay
110	135	25	Cemented gravel (brown)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 110 to 135 ft.

Other aquifers _____

First water at 110 feet.

Casing perforated

from 112 to 120 ft.

Size of perforations

3/16" x 3" with 6" centers and 4 slots to the round.



