

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2744  
 Rec. June 8 1953  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner MONAZI LINDLEY Driller MEL MEYER  
 Address Cinnabar Hill Ranch Sparks, Address 120 Moana Lane Reno Lic. No. 3  
Spanish Springs Rd. Nevada  
 Location of well: 1/4 Sec. 20, T. 20 N/S, R. 10 E, in Washoe County

Water will be used for Home Total depth of well 127

Size of drilled hole 8" Weight of casing per linear foot 16#

Thickness of casing 3/16" Temp. of water Warm

Diameter and length of casing 6 1/4" X 226'6"  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 26

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well 5-2-53 Date of completion of well 5-18-53

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Sandy Clay Brown
18	28	10	Gravel and Clay
28	40	12	Boulders
40	65	25	Brown Clay Boulders
65	70	5	White Clay Boulders
70	86	16	Red Brown Clay, Boulders
86	95	9	Brown Clay, Broken Rock
95	127	32	" " " "
127	133	6	White Clay
133	135	2	Brown Clay, Rocks
135	138	3	" " "
138	147	9	White Clay
147	156	9	Blue Clay
156	184	28	Blue Rock, Hard Broken
184	225	29	Gray Rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 140 to 160 ft.

Other aquifers 26

First water at 26 feet.

Casing perforated

from 224 to 184 ft.

Size of perforations

5" x 1/4

