

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA



Log No. 2258V
Rec. June 29 1953
Well No.
Permit No.

Owner Mrs Nell Daley Driller J. Champion - C. Pulate
Address Rte 1 Box 568 Address Rte 1 Box 352 Lic. No. 29
Location of well: $\frac{1}{4}$ $\frac{1}{4}$ Sec. 6, T. 18 N. 8 E, R. 20 E, in South Virginia Town Washoe County
or
Water will be used for Domestic Total depth of well 170 ft.
Size of drilled hole 6 inch Weight of casing per linear foot 14 lb.
Thickness of casing 3/16 Temp. of water 58°
Diameter and length of casing 6" - 120 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 14 ft.
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well Mar 17-53 Date of completion of well Mar 26-53
Type of well rig B & 24 24 L. J puller.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	32		Clay + Small gravel + sand
32	38		Clay + Sand
38	48		sand + some water
48	55		dense clay + gravel
55	64		sand + clay
64	70		clay
70	78		clay
78	84		sandy clay
84	90		tight clay + gravel
90	118		gravel water
118	123		Blue clay
123	125		yellow clay
125	150		clay
150	165		sand
165	170		clay (Blue)

Water-bearing Formation, Casing Perforations, Etc.
Lower 26' perforated
Chief aquifer (water-bearing formation)
from 90 to 118 ft.
Other aquifers 38' - 48'
.....
.....
.....
First water at 38' feet.
Casing perforated
from 94 to 120 ft.
Size of perforations
1/8 x 1/4

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed _____
Well Driller

By John Champus

License No. 29

Dated June 27, 1963

(Not to be filled in by Driller)
