

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2292
 Rec. July 17 1953
 Well No.
 Permit No.
Do not fill in

COPY

U. S. A., Dept. of Interior
 Owner Bureau of Land Management Driller Geo. W. Norcutt
 Address Carson City, Nev Address Fallon, Nev Lic. No. 33
 Location of well: SE $\frac{1}{4}$ 1/4 SE $\frac{1}{4}$ 1/4 Sec. 18, T. 20 N, R. 21 E, in. Washoe County
 or
 Water will be used for Total depth of well 96'
 Size of drilled hole 8" Weight of casing per linear foot 20#
 Thickness of casing 1/2" Temp. of water
 Diameter and length of casing 6" 96'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 65'
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well June 22, 1953 Date of completion of well July 3, 1953
 Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	red clay
3	14	11	gravel and boulders
14	27	13	sandy clay
27	33	6	gravel and clay
33	36	3	sandy clay
36	46	10	gravel
46	59	13	sandy clay
59	74	15	Clay
74	78	4	water sand
78	86	8	sandy clay
86	95	9	gravel
95	96	1	clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 86 to 95 ft.
 Other aquifers from 74 to 78'

First water at 74' feet.

Casing perforated
 from 74' to 96' ft.

Size of perforations
1/8 x 2

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

(Not to be filled in by Driller)

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed /s/ Geo. W. Norcutt
Well Driller

By

License No. 93

Dated July 3, 1953


