WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2302
Rec. JULY 22 1953
Well No.
Permit No.
Do not fill in

Owner: S. S JAKSICK
Driller: CHANDA DRILLING CO
Address: CRYSTAL BAY NEVADA
Address: KINGS BEACH, CALIF. Lic. No. 85
Location of well: ¼ ¼ Sec. 23, T. 16 N/S, R. 18 E, in WASHOE County
or INCLINE BEACH SUBDIVISION Lot. 5.
Water will be used for: DOMESTIC
Total depth of well: 155 ft.
Size of drilled hole: 8 INCH DIA.
Weight of casing per linear foot: 10 GA.
Thickness of casing: 10 GA
Temp. of water: COLD
Diameter and length of casing: 8 INCH X 155 FT.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure: —
If nonflowing well give depth of standing water from surface: 22 ft.
If flowing well describe control works: —
(Type and size of valve, etc.)
Date of commencement of well: 7/4/53
Date of completion of well: 7/12/53
Type of well rig: CABLE — BUCYRUS ERIE

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	29'	29'	SAND & CLAY MIX
29'	153'	124'	LOOSE SAND & WATER
153'	155'	2'	HARD PAN

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 128' to 153' ft.

Other aquifers

First water at 29' feet.

Casing perforated
from 128' to 153' ft.

Size of perforations
1/16" x 2"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 IN.	0	155'	155'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

SAND PUMPED + TESTED WELL BEFORE INSTALLING PUMP

WELL PRODUCED 8,600 GALS PER HR. + STATIC LEVEL DROPED TO 26 FT.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed L. H. Chandler
Well Driller

By.....

License No. 85

Dated 7/15/53, 19..

JUL 22 53

(Not to be filled in by Driller)