


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Copy to cc.



2314
 Log No. _____
 Rec. 7-28 19 53
 Well No. _____
 Permit No. 15168 to be issued
 Do not fill in 15168

Owner Frank Garbers Driller C. F. Daniels

Address Tonopah Rd. Near Vages Drive Address Box 554 Lic. No 136

Location of well: SW 1/4 SW 1/4 Sec 20, T20 N/S, R61 E, in Clark County

or from well at SW cor. of sec. 20. 2000 S 49° 25' W. 868 ft.

Water will be used for quasi-municipal Total depth of well 400

Size of drilled hole 8 inch Weight of casing per linear foot 11.6

Thickness of casing 10 Ga. Temp. of water medium

Diameter and length of casing 8 inch 20 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 2 ft.

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well June 16, 1953 Date of completion of well July 16, 1953

Type of well rig Armstrong

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
15	15	15	Sand & Brown dirt	Chief aquifer (water-bearing formation)
	35	20	Cleatchey Rock	from <u>350</u> to <u>400</u> ft.
35	40	5	some sand & gravel water	Other aquifers _____
40	135	95	mud (brown)	_____
135	350	215	" "	_____
350	400	50	light red mud. some sand, water raised to 2 ft.	First water at <u>16</u> feet.
				Casing perforated from <u>80</u> to <u>100</u> ft.
				Size of perforations <u>1/4</u> by <u>81</u> in.

