Log No. 2320
Rec. 19
Well No. —
Permit No. 14926
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Copy to CC

Owner: Larry Johnson
Driller: Effinger Bros.
Address: Sante Fe Motel
Address: 212 Anderson Lane
Lic. No. 105

Location of well: SW¼ NW¼ Sec. 28, T. 21 N/S, R. 61 E, in Clark County
or Los Angeles Highway

Water will be used for: Quasi-Muncipal
Total depth of well: 250 feet

Size of drilled hole: 12 Inch
Weight of casing per linear foot: 16.9 lbs

Thickness of casing: 3/16
Temp. of water: 72°

Diameter and length of casing: 8" to 160'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 2' from top of casing 7/29/53 10 GPM

If nonflowing well give depth of standing water from surface: + 5.5 M.P. Cement 3 lb at Surface

If flowing well describe control works: (Type and size of valve, etc.)

Date of commencement of well: July 5, 1953
Date of completion of well: July 8, 1953

Type of well rig: "71 Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
90	100	10	Gravel
100	114	14	Clay
114	117	3	Sand Stone
117	126	9	Yellow Clay
126	129	3	Gravel (Water)
129	130	1	White Clay
130	137	7	Conglomerate
137	142	5	Red Clay
142	144	2	Sand Stone
144	147	3	Clay
147	151	4	Sandy Clay
151	156	5	Sand Stone
156	157	1	Clay
157	159	2	Gravel (Water)
159	165	6	Clay
165	168	3	Sand Stone
168	179	11	Clay
179	186	7	Clay & Gravel
186	194	8	Sandy Clay
194	198	4	Gravel (Water)
198	200	2	Red Clay & Gravel
200	202	2	Sand Stone
202	215	13	Red Sticky Clay
215	218	3	Clay & Gravel
218	225	7	Gravel (Water)
225	227	2	Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 234 to 240 ft.

Other aquifers: 218-225
194-198
157-159
126-129

First water at ____ feet.

Casing perforated
from 100 to 160 ft.

Size of perforations
1/8" X 12"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
227	231	4	Gravel
231	234	3	Clay
234	240	6	Gravel (Water)
240	250	10	Clay & Gravel

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
5 5/8" OD	0	160	160	Cemented from 0 to 31 feet
				Perforated from 100 to 160 feet
				1 3/4 Yds Ready-Mix

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.
Well Driller

By A. F. Effinger

License No. 105

Dated July 8, 1953, 19

(Not to be filled in by Driller)