Log No. 2322
Rec. 19
Well No.
Permit No. 14146
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Copy to cc

Owner: Joe Blumenthal
Driller: Effinger Bros.
Address:
Address: 212 Andersom Lane Lic. No. 105
Location of well: NW ¼ NW ¼ Sec. 33, T. 21 N/S, R 61 E, in Clark County
or Los Angeles Highway
Water will be used for: Quasi-Muncipal
Total depth of well: 250 feet
Size of drilled hole: 12 Inch
Weight of casing per linear foot: 14.87 Lbs
Thickness of casing: 10 Guage
Temp. of water:
Diameter and length of casing: 10" OD 200 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 17' 11" from top of casing
If flowing well describe control works: 7/29/53 - 21.64. 1¼" Nipple 0.25 Above Ground Clak
(Type and size of valve, etc.)
Date of commencement of well: June 23, 1953
Date of completion of well: July 3, 1953
Type of well rig: "71 Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Yellow Clay & Gravel
6	18	12	White Clay
18	24	6	Cement Gravel
24	27	3	White Clay & Gravel
27	34	7	Calichie
34	36	2	Gravel (Water)
36	39	3	White Clay
39	43	4	Gravel (Water)
43	45	2	Red Clay
45	51	6	Gravel
51	66	15	Red Clay
66	73	7	Gravel (Water)
73	76	3	Red Clay
76	83	7	Gravel
83	88	5	Red Clay
88	93	5	Gravel (Water)
93	97	4	Sand Stone
97	100	3	Yellow Clay
100	112	12	Gravel (Water)
112	115	3	Yellow Clay
115	118	3	Gravel
118	126	8	Red Sand Stone
126	129	3	Red Clay
129	133	4	Red Sand Stone
133	141	8	Red Sandy Clay
141	144	3	Gravel
144	151	7	Brown Sand Stone

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 240 to 245 ft.
Other aquifers 164-169
100-112
88-93
66-73
39-43
34-36

First water at 34 feet.

Casing perforated
from 85 to 200 ft.

Size of perforations
1/8" X 12"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
151	157	6	Sticky Clay
157	160	3	Brown Sand Stone
160	164	4	Clay
164	169	5	White Sand Stone (Water)
169	184	15	Red Clay
184	191	7	Red Clay & Gravel
191	205	14	Red Clay
205	211	6	Sand Stone
211	230	19	Red Clay & Gravel
230	240	10	Sand Stone
240	245	5	Black Gravel & Sand (Water)
245	246	1	Red Clay
246	250	4	Sand Stone

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
10"OD	0	200	200	Cemented from 0 to 85 feet
				Perforated from 85 to 200 feet
				5½ Yds of Ready-Mix

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.
Well Driller

By O. F. Effinger

License No. 105

Dated July 3, 1953

(Not to be filled in by Driller)