

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

+
 Log No. 2354
 Rec. Aug 19 1953
 Well No. 2
 Permit No. _____
Do not fill in

Owner Delbert Young Driller Gloyd Hastings
 Address Baker Nevada Address Hurricane Utah Lic. No. 150
 Location of well: NW 1/4 SE 1/4 Sec 25, T10 N 8, R 70 E, in Whitestone County
 or N.W. 1/4 of S.E. 1/4 of Sec. 25 T10 N R 70 E.
 Water will be used for Irrigation Total depth of well 70'
 Size of drilled hole 16 3/8" Weight of casing per linear foot 22 lbs.
 Thickness of casing 3/16" Temp. of water _____
 Diameter and length of casing 16 3/8" 70'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 8'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well 7/28/53 Date of completion of well 8/3/53
 Type of well rig Speed Star - Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Clay
5	11	6	Dry Gravel
11	32	21	Water Gravel
32	40	8	Clay
40	41	1	Gravel
41	50	9	Clay
50	54	4	Gravel
54	70	16	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 11 to 32 ft.

Other aquifers 40-41

50-54

First water at 11 feet.

Casing perforated

from 11 to 32 ft.

40-41 50-54

Size of perforations

1/4" X 2"



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16 3/8	0	70'	70'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Floyd Hastings
Well Driller

By Same

License No. 150

Dated Aug 14, 1933

(Not to be filled in by Driller)
