WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2340
Rec. Aug. 17 1953
Well No.
Permit No.
Do not fill in

Owner: GEORGE FETTIE
Address: CARSON CITY
Driller: HARVEY MEYER
Address: CARSON CITY Lic. No. 10

Location of well: SW ¼ SE ¼ Sec. 20, T. 14 N/S, R. 20 E, in ~~CARSON~~ Douglas County

or

Water will be used for: DOMESTIC
Total depth of well: 71' 6"

Size of drilled hole: 6"
Weight of casing per linear foot: 14 L 135.

Thickness of casing: 3/16
Temp. of water: Cool

Diameter and length of casing: 6" — 71' 6"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: no

If nonflowing well give depth of standing water from surface: 21'

If flowing well describe control works: no
(Type and size of valve, etc.)

Date of commencement of well: JULY 14
Date of completion of well: JULY 15

Type of well rig: CABLE TOOLS

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	SAND CLAY.
12	16	4	HARD PAN.
16	27	11	SANDY CLAY.
27	30	3	WATER SAND.
30	57	17	SANDY CLAY.
57	65	8	WATER SAND.
65	71½	6½	SANDY CLAY.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 57 to 65 ft.

Other aquifers

First water at 27' feet.

Casing perforated
from 0 to 20 ft.

Size of perforations
1/8

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL WILL MAKE 1200 GAL PER HOUR BAILING TEST.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Mayer
Well Driller

By Harry Mayer

License No. 10

Dated July 15, 1953

(Not to be filled in by Driller)