WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2382
Rec. Oct. 10 1953
Well No.
Permit No.
Do not fill in

Owner: M. J. Krupka
Driller: J. C. Faretto & Son
Address: Rt. 2 Box 693, Reno, Nev.
Address: 736 Humboldt St., Reno Lic. No. 2

Location of well: SE¼SE¼ Sec. 16, T. 19 N/S, R 19 E, in Truckee Meadows, Washoe County
or mile west of Reno High School on Mayberry Drive

Water will be used for: Domestic
Total depth of well: 82'-06"

Size of drilled hole: 6 inch
Weight of casing per linear foot: 18.97 lbs

Thickness of casing: .280 of an inch
Temp. of water: 58°

Diameter and length of casing: 6" inside diameter. 8'-09" to 11'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 30'-00"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: September 4, 1953
Date of completion of well: September 11, 1953

Type of well rig: Cable Too Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Bolders, rocks, sand with soil. Loose.
25	40	15	Yellow clay, rocks, with coarse sand + gravel. Tight.
40	51	11	Yellow clay with coarse sand + gravel. Tight.
51	66	11	1st water. Water level 37'-06". Little water. Yellow clay with coarse sand + gravel. Soft.
66	76	10	Yellow clay with coarse sand + gravel.
76	83	7	2nd water. Little water. Yellow clay with coarse sand + gravel.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 83 to 87 ft.

Other aquifers 76 to 83
51 to 66

First water at 51 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
83	87	4	3rd water. Water level 30'-00". Little water. Yellow clay with coarse sand + gravel.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	3'-11"	82'-06"	83'-05"	Standard black new pipe. Short patterned shoe. Pipe welded with ¼"x 5" welding couplings.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

0 to 51 ft black sand. 51 ft to 87 ft gray colored sand with brown colored material. Gravel washed + smooth. Well cleaned and tested with compressor 1.5 gal per minute 7'-09" drawdown.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated October 7, 1953

(Not to be filled in by Driller)