

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2382 ✓
 Rec. Oct. 10 1953.
 Well No. _____
 Permit No. _____
Do not fill in

Owner Jack Kivett Driller J.C. Faretto & Son
 Address General Delivery, Sparks, Nev. Address 736 Humboldt St., Reno Lic. No.
 Location of well: N.W. 1/4 Sec. 34, T. 18 N., R. 20 E., in Truckee Meadows, Washoe County
or. mile north east from Steamboat on the old Virginia Road.
 Water will be used for Domestic Total depth of well 110 ft.
 Size of drilled hole 6 inch Weight of casing per linear foot 16.89
 Thickness of casing .188 Temp. of water 62°
 Diameter and length of casing Outside diam. 6 5/8". 8'-09" to 11'-03" lengths.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure. _____
 If nonflowing well give depth of standing water from surface 35'-00"
 If flowing well describe control works. _____
 (Type and size of valve, etc.) _____
 Date of commencement of well September 23, 1953 Date of completion of well October 2, 1953.
 Type of well rig Cable Tool Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Soil, stony & rocks.
8	12	4	Red clay, rocks & stony.
12	25	13	Red clay.
35	50	15	Yellow clay, soft.
50	60	10	1st. water. Water level 35'-00". Little water. Yellow clay with fine sand a little coarse gravel.
60	73	13	Yellow clay. Soft.
73	77	4	2nd water. Little water. Yellow clay with coarse sand a little coarse gravel.
77	90	13	Yellow clay. Hard.
90	95	5	Change in color of clay. Hard.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 95 to 110 ft.

Other aquifers 73 to 77
50 to 60

First water at 50 feet.

Casing perforated
 from 50 to 60 ft.
73 to 77

Size of perforations
3/8" x 1 1/2"

