

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2702  
 Rec. Oct. 26 19 53  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Henry Shulte Driller Mel Meyer  
 Address Shulte Service Gardnerville, Nev. Address 120 Moana Lane Reno Lic. No. 3  
 Location of well: SE 1/4 SE 1/4 Sec. 32, T. 3 N. R. 20 E, in Douglas County  
 or Between Minden and Gardnerville, Nevada  
 Water will be used for Service Station Total depth of well 152  
 Size of drilled hole 6" Weight of casing per linear foot 19#  
 Thickness of casing 5/16" Temp. of water Cold  
 Diameter and length of casing 6" ID X 152'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface 10  
 If flowing well describe control works.....  
 (Type and size of valve, etc.)  
 Date of commencement of well 9-22-53 Date of completion of well 9-30-53  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Clay and Rocks
20	40	20	Clay and Rocks
40	72	32	Sand and Clay
72	103	31	Sand and Clay
103	110	7	Sand and Clay
110	120	10	Sand, Gravel, and Water
120	130	10	Sand, Gravel, and Clay
130	145	15	Sand, Gravel, and Water
145	152	7	Sand and Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 110 to 152 ft.

Other aquifers.....

40

First water at 40 feet.

Casing perforated

from 90' to 150 ft.

Size of perforations

3/8 X 2 1/2



