

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2406
 Rec. Nov. 9 1953
 Well No.
 Permit No. 15381
Do not fill in

Owner Combined Metals Reduction Co. Driller J. D. Hill
 Address Pioche, Nevada Address Box 694, Ely, Nevada Lic. No. 14
 Location of well: NE 1/4 NW 1/4 Sec 29, T. 11N, S. R. 68E, in White Pine County
 or.....
 Water will be used for Mining Total depth of well 353
 Size of drilled hole 8 in. Weight of casing per linear foot 19#
 Thickness of casing 1/4 in. Temp. of water.....
 Diameter and length of casing 8 in. x 347 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface 250 ft.
 If flowing well describe control works.....
 (Type and size of valve, etc.)
 Date of commencement of well Oct. 21, 1953 Date of completion of well Nov. 7, 1953
 Type of well rig Churn drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	268	268	Cemented gravel
268	269	1	Gravel (Water)
269	284	15	Cemented gravel
284	307	23	
284	285	1	Sand and gravel
286	307		Cemented gravel
307	308	1	Sand and gravel
309	322	13	Cemented gravel
323	324	1	Sand and gravel
324	335	11	Cemented gravel
335	336	1	Sand and gravel
336	343	7	Cemented gravel
343	344	1	Sand and gravel
344	353	9	Sand and gravel Cemented

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 268 to 269 ft.

Other aquifers

284 to 285

323 to 324

335 to 336

343 to 344

First water at 268 feet.

Casing perforated
 from 217 to 347 ft.

Size of perforations
1/4 x 6



