

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 12 2437
 Rec. Dec. 17 1953
 Well No. I
 Permit No. 164
Do not fill in

Owner Richard & Harold Herz Driller George Pounder

Address Rt. 1 Box 445A, Reno, Nevada Address S. & M. Ranch, Reno Lic. No. 164

Location of well: 1/4 1/4 Sec. 20, T. 12N, R. 2E, in Washoe County

Water will be used for Domestic Total depth of well 80'

Size of drilled hole 6" Weight of casing per linear foot 18 pounds

Thickness of casing 1/4" Temp. of water Approx 50 degrees

Diameter and length of casing 6" 12' lengths
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 22'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well November 15, 1953 Date of completion of well November 19, 1953

Type of well rig Keystone

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	8	8	Boulders	
8	72	64	Sand & Gravel	Chief aquifer (water-bearing formation) from <u>20'</u> to <u>80</u> ft. Other aquifers <u>Gravel</u> <u>Sand</u>
				First water at <u>32</u> feet.
				Casing perforated from <u>32</u> to <u>80</u> ft.
				Size of perforations <u>6 X 1/4</u>



