WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2457
Rec. Jan 6 1954
Well No.
Permit No. 17601
Do not fill in

Owner Arthur V Heller Driller O. J. Pearson

Address ~~1502~~ Flannagan Nevada Address 1502 First Susanville Calif Lic. No. 166

Location of well: N 1/2 of SW 1/4 SE 1/4 of SW 1/4 ¼ ¼ Sec. , T. N/S, R. E, in Warsaw County

Sec 24 Township 27 Range 18 13

or Nevada

Water will be used for Stock water Total depth of well 200'

Size of drilled hole 8" Weight of casing per linear foot 26 lb

Thickness of casing 3/8" Temp. of water

Diameter and length of casing 8" — 40'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 20'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Jan 3 - 1954 Date of completion of well Jan 4 - 1954

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3'	3'	Surface
3'	15'	12'	Sandy yellow clay
15'	18'	3'	Fine yellow sand
18'	23'	5'	yellow clay
23'	36'	13'	Hard Packed yellow sand
36'	45'	9'	soft yellow clay
45'	52'	7'	Hard yellow clay
52'	58'	6'	Hard sand Rock
58'	62'	4'	Hard Blue clay
62'	135'	73'	Layers of sand & Blue clay
135'	200'	65'	soft Black Lava Rock, water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 135' to 200' ft.

Other aquifers None

First water at 135' feet.

Casing perforated

from None to ft.

Size of perforations

None

(OVER)

919