WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2452
Rec. Jan 11 1954
Well No.
Permit No. 15452 - 18742
Do not fill in 36156 36155

Owner: Gus Knezevich
Driller: N D Kelly
Address: Humbolt Hotel
Address: 111 - 4th St Winnemucca Lic. No. 157

Location of well: SE 1/4 SW 1/4 Sec. 30, T 26 N/S, R 38 E, in Humbolt County

or

Water will be used for: Irrigation
Total depth of well: 495 Ft

Size of drilled hole: 14 inch
Weight of casing per linear foot: 18 lb

Thickness of casing: 10 Ga
Temp. of water: 60

Diameter and length of casing: 14 4" 495'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 70 Ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 9-1-53
Date of completion of well: 10-28-53

Type of well rig: Home Made

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Sandy Soil
25	115	90	Gravel
115	180	65	Clay & Gravel
180	200	20	Gravel
200	250	50	Clay
250	260	10	Gravel
260	480	220	Clay
480	490	10	Gravel
490	495	5	Lava

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 480 to 495 ft.

Other aquifers

First water at 90 feet.

Casing perforated

from 80 to 495 ft.

Size of perforations

1/4 x 4"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump test 1400 GPM drawdown 70' to 80'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Norman D Kelly
Well Driller

By Wm. Flynn

License No. 125

Dated 11-8, 19

OFFICE STATE ENGINEER
JAN 11 '54
RECEIVED
ANS

(Not to be filled in by Driller)