

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2470  
 Rec. 2/9/54 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner W. Ott Driller George Pounder

Address Black Springs, Nevada Address Rt. 1 Box 445A, Reno Lic. No. 164

Location of well:  $\frac{1}{4}$  Sec. 16, T20 N/S, R19 E, in Washoe County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 110'

Size of drilled hole Six Inch Weight of casing per linear foot 18

Thickness of casing  $\frac{1}{4}$ " Temp. of water 40

Diameter and length of casing 6" 10 foot lengths  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 18 feet

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well January 11, 1954 Date of completion of well Jan. 16, 1954

Type of well rig Keystone Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	65	65	Gravel, Clay	Chief aquifer (water-bearing formation) from <u>65</u> to <u>110</u> ft. Other aquifers <u>Gravel, Sand</u> _____ _____ _____ First water at <u>65</u> feet. Casing perforated from <u>60</u> to <u>110</u> ft. Size of perforations <u>6 X <math>\frac{1}{4}</math>"</u>
65	77	12	Gravel	
77	98	21	Sand, Gravel	
98	110	12	Gravel	



