

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2472
 Rec. Feb 15 1954
 Well No. _____
 Permit No. 15206
Do not fill in

Owner Joe TATE Driller Cribbs Rodgers I56

Address 3000 Palomino Lane Address 3000 Palomino Lane Lic. No. 156

Location of well: E 1/4 1/4 Sec. 13, T. 21 N/S, R. 61 E, in _____ County
 or E 1/4 SE. 1/4 NW 1/4 Sec 13 T 21 S N 61 E

Water will be used for Domestic Total depth of well 400

Size of drilled hole 8 In. Weight of casing per linear foot 15

Thickness of casing 10 G.A. Temp. of water _____

Diameter and length of casing 120 Ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface at surface 1-28/54 - 120' M.P. to surface

If flowing well describe control works 4 In outlet at surface
(Type and size of valve, etc.)

Date of commencement of well Jan. 15 Date of completion of well Jan 28 54

Type of well rig SPUDDER

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
00	9	9	sand gravel	
9	15	6	Colechie	
15	60	45	light brown clay	
60	64	4	Gravel water	Chief aquifer (water-bearing formation) from <u>250</u> to <u>260</u> ft.
64	110	46	pink sandy clay	
110	125	15	white solid shale	Other aquifers <u>60</u> <u>110</u>
125	165	40	pink sandy clay	raise in water
165	250	85	tough lavender clay	at <u>265</u>
250	260	10	decomposed lime gravel	
260	300	40	tough lavender clay	
300	365	65	pink sandy clay	
365	400	35	red clay	
			this well flowing about 10 G.P.M.	First water at <u>60</u> feet. no perf Casing perforated from _____ to _____ ft. Size of perforations _____