WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2490
Rec. Mar. 16 1954
Well No.
Permit No.
Do not fill in

Owner: GROVER A. YOUNG Driller: HARVEY MEYER
Address: WASHOE LAKE Address: CARSON CITY Lic. No. 10
Location of well: NW ¼ NW ¼ Sec. 2, T. 16 N/S, R. 19 E, in WASHOE County
or
Water will be used for: DOMESTIC Total depth of well: 106'
Size of drilled hole: 6" Weight of casing per linear foot: 19 LBS.
Thickness of casing: 5/16 Temp. of water: COOL.
Diameter and length of casing: 6" — 106'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure: 3 GAL PER MINUTE
If nonflowing well give depth of standing water from surface: ✓
If flowing well describe control works: 1 FOOT NIPPLE OUT.
(Type and size of valve, etc.)
Date of commencement of well: MAR. 12 Date of completion of well: MAR. 14th
Type of well rig: CABLE TOOLS.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	SOIL & R.
5	20	15	SANDY CLAY.
20	25	[illegible]	GRANIT. WATER.
25	75	[illegible]	SANDY BLUE CLAY
75	80	[illegible]	SAND. WATER.
80	85	[illegible]	BLUE SANDY CLAY
85	100	[illegible]	SAND. WATER.
100	106	[illegible]	SANDY. CLAY.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) from 85 to 100 ft.
Other aquifers
First water at 20' feet.
Casing perforated from 86 to 106 ft.
Size of perforations 1/8.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well is Flowing 3 Gal
Per minite

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harvey Meyer
Well Driller

By Harvey Meyer

License No. 10

Dated MAR 14, 19 54

OFFICE STATE ENGINEER
MAR 15 '54
RECEIVED
ANS.

(Not to be filled in by Driller)