WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2514
Rec. April 1 1954
Well No.
Permit No.
Do not fill in

Owner ED STEINER Driller GEORGE POUNDER

Address 333½ - 13th ST Sparks Nev Address Rt. 1 Box 445A, RENO Lic. No. 164

Location of well: ¼ ¼ Sec. 16, T 19 N/S, R 20 E, in WASHOE County

or

Water will be used for DOMESTIC Total depth of well 68'

Size of drilled hole 6" Weight of casing per linear foot 18 pounds

Thickness of casing ¼" Temp. of water 45°

Diameter and length of casing 6" Inside 10' lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 2/26/54 Date of completion of well 3/3/54

Type of well rig KEYSTONE

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	ROCK.
25	41	16	RED SAND, GRAVEL
41	47	6	GRAVEL
47	55	8	CLAY, GRAVEL
55	68	13.	BLUE CLAY SHALE

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 25 to 55 ft.

Other aquifers GRAVEL

First water at 35 feet.

Casing perforated

from 41 to 68 ft.

Size of perforations

¼"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
				NONE.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

PUMP NOT INSTALLED.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed George Pounder
Well Driller

By Richard A. Hey

License No. 44

Dated March 28, 19

OFFICE STATE ENGINEER
APR 0 1 '54
RECEIVED

(Not to be filled in by Driller)