WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2534
Rec. April 28 19 54
Well No.
Permit No.
Do not fill in

Owner Homer Cox Driller Davis Drilling Co
Address 1035 Desert Lane Las Vegas Address 1638 Maryland Ave Wasatch Cal Lic. No. 96

Location of well: SE ¼ ¼ Sec., T. N/S, R. E, in Clark County

or E½ SE¼, SW¼ TW 21 R-60 E SE 1

Water will be used for Domestic Total depth of well 298

Size of drilled hole 6" Casing Weight of casing per linear foot 9 lb

Thickness of casing 12 Gauge Temp. of water

Diameter and length of casing 6" set all the way
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 90 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 3-26-54 Date of completion of well 3-30-54

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	33	33	top soil
33	45	12	Rock imbedded in clay
45	188	143	Rock - ~~[illegible]~~ Boulders
188	232	44	Boulders.
232	298	66	Boulder + Sand.

~~[illegible]~~

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 232 to 298 ft.

Other aquifers

First water at 221 feet.

Casing perforated

from 200 to 298 ft.

Size of perforations

3/16" X 3"

(OVER)

910

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
				Cemented Top 60 ft.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Well Driller

By [illegible]

License No. [illegible]

Dated 4-18-, 1954

OFFICE STATE ENGINEER
APR 25 '54
RECEIVED
ANS

(Not to be filled in by Driller)