WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2537
Rec. May 3 19 54
Well No.
Permit No.
Do not fill in

Owner: Kendrick Johnson Driller: J. C. Faretto & Son
Address: P.O. box 2222; Reno, Nev. Address: 736 Humboldt St., Reno Lic. No. 2
Location of well: NW¼NE¼ Sec. 13, T. 18 N/S, R. 19 E, in Truckee Meadows, Washoe County
or about 2 miles south on Thomas Greek Road from Reno-Carson Highway.
Water will be used for: Domestic Total depth of well: 47 ft
Size of drilled hole: 6 inch Weight of casing per linear foot: 18.97 Lbs.
Thickness of casing: .280 of an inch Temp. of water: 54°
Diameter and length of casing: 6" inside diameter. 10'-06" to 11'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 3'-10"
If flowing well describe control works:
(Type and size of valve, etc.)
Date of commencement of well: March 31, 1954 Date of completion of well: April 14, 1954
Type of well rig: Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Hardpan & rocks.
15	18	3	Yellow clay. Soft.
18	24	6	1st. water. Water level 10'-00". Little water. Clay with fine to coarse granite sand.
24	30	6	Yellow clay.
30	39	9	2nd water. Little water. Clay with fine to coarse sand & a Little gravel.
39	42	3	Rocks & clay
42	47	5	3rd water. Little water. Cementation, water bearing sand between cemented stratas. Hard.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 30 to 39 ft.
Other aquifers: 42 to 47 ft.
18 to 24 ft.

First water at 18 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	1'-06"	41'-07"	43'-01"	Standard black pipe. Pipe welded with ¼" x 3" welding couplings. New pipe used. Short pattern drive shoe.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Sand material granite sand with a little black sand. Cementation material at 42 to 47 ft very hard. Well cleaned & tested with compressor 5'-03" drawdown pumping 16.5 gal. per minute.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated April 28, 1954

OFFICE STATE ENGINEER
MAY - 3 54
RECEIVED

(Not to be filled in by Driller)