WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2571
Rec. June 3 1954
Well No.
Permit No.
Do not fill in

Owner J. Butner Driller George Pounder

Address Snare Hill Reno Verdi Highway Address Rt 1 Box 445A Reno Nevada Lic. No. 164

Location of well: ¼ ¼ Sec. 32, T. 19 N/S, R. 19 E, in Washoe County County

or

Water will be used for Domestic Total depth of well 115 ft

Size of drilled hole 8" Weight of casing per linear foot 20 pounds

Thickness of casing 3/8" Temp. of water 50°

Diameter and length of casing 8" Inside 10 foot lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 40 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well April 22nd Date of completion of well May 1, 1954

Type of well rig Keystone

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Boulders & Gravel
40	60	20	Clay & Gravel
60	115	55	Water Sand & Coarse Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 115 ft.

Other aquifers Sand & Gravel

First water at 55 feet.

Casing perforated

from 50 to 115 ft.

Size of perforations

1/4"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump NOT Installed

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed George Pounder
Well Driller

By Richard Herz

License No. 164

Dated June 1, 1954

(Not to be filled in by Driller)