WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

17833

Now owned by Mesquite Town Water Co,

Log No. 2582
Rec. June 15 19[illegible]
Well No.
Permit No. 18604-17833
Do not fill in

Owner Dri-State Metals Driller Victor Collins

Address Mesquite, Nevada Address Lioche, Nevada Lic. No. 177

Location of well: NE ¼ SW ¼ Sec. 21, T. 13 N/S, R. 71 E, in Clark County

or

Water will be used for Milling Total depth of well 200

Size of drilled hole 8 in. Weight of casing per linear foot

Thickness of casing 10 guage Temp. of water

Diameter and length of casing 8 in. for 170 ft - 6 in. for 30 feet
(Casing 12" in diameter and under give inside diameter; casing 10" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 120

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 3-54 Date of completion of well May 23-54

Type of well rig cable - buoyrus

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	42	42	coarse gravel
42	140	98	red sand
140	143	[illegible]	water bearing gravel
143	195	52	red-sand + clay-mixed
195	200	5	sand, coarse gravel

Water-bearing Formation, Casing Perforations, Etc.
140-143

Chief aquifer (water-bearing formation)
from 140 to 143 ft.

Other aquifers 195 to 200

First water at 140 feet

Casing perforated
from 122 to 200 ft.

Size of perforations
⅛" by 12" long

(OVER)

918