

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 2610
 Rec. June 18 1954
 Well No. _____
 Permit No. 18420
 Do not fill in

Owner Sierra Oxygen Co Driller John Champion
 Address 1500 E. 2nd St. Reno Address Rt. 1. Box 352 Reno Lic. No. 29
 Location of well: NW⁴ SE⁴ 12 1/4 Sec. 5, T. 12 N/S, R. 10 E, in Washoe County
 or 1500 E. 2nd St. Reno
 Water will be used for Domestic Total depth of well 130 feet
 Size of drilled hole 8" Weight of casing per linear foot _____
 Thickness of casing 8" Standard Temp. of water _____
 Diameter and length of casing 8" - 128'-6"
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 21 feet
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well July 16-1953 Date of completion of well Aug. 7-1953
 Type of well rig Spudder (Bueyrus Eric 22-T)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	42	42	Sand gravel & Boulders
42	63	21	Sand " " "
63	70	7	" & Gravel
70	78	8	" " "
78	95	17	" Gravel & small Boulders within Clay Sh.
95	121	26	Clayish gravel & clay
121	130	9	white sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 120 to 130 ft.

Other aquifers 42-78

shut out

First water at 42 feet.

Casing perforated from 105 to 125 ft.

Size of perforations

3/16" x 6" slots

