WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2618
Rec. 6/18 1967
Well No.
Permit No.
Do not fill in

Owner: Steamboat Hot Springs Driller: John Champion
Address: " " " Address: So. Va. Rd. Reno Lic. No. 29
Location of well: ¼ ¼ Sec. , T. 18 N/S, R. E, in Washoe County
or Steamboat Hot Springs.
Water will be used for: Baths. Total depth of well
Size of drilled hole: 6" Weight of casing per linear foot
Thickness of casing: Standard Temp. of water
Diameter and length of casing: 6" 41 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure: Est. 110 gp. m. Pressure?
If nonflowing well give depth of standing water from surface
If flowing well describe control works: Installed 6" Control Valve & T's.
(Type and size of valve, etc.) cemented Casing
Date of commencement of well: Oct. 27 Date of completion of well: Oct. 31.
Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	5	Built up Crust
8	34	16	Blue Shale & gravel
34	37	3	Caprock
37	47	10	Blue lime, Boulders & Blue Mud
47	49½	2½	Hard shell
49½	67	17½	Blue shale w/ thin Rock strks.
67	79	12	Blue Shale w/ lime st.
79	82	3	Hard lime.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 37 to 47 ft.
Other aquifers

First water at 37 feet.

Casing perforated
from — to — ft.

Size of perforations

(OVER)

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2618
Rec. 6/18 1954
Well No.
Permit No.
Do not fill in

Owner Steamboat Hot Springs Driller John Champion

Address " " " Address So. Va. Rd. Reno. Lic. No. 29

Location of well: ¼ ¼ Sec. , T. 18 N/S, R. 20 E, in Washoe County

or Steamboat Hot Springs.

Water will be used for Baths. Total depth of well

Size of drilled hole 6" Weight of casing per linear foot

Thickness of casing Standard Temp. of water

Diameter and length of casing 6" 41 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Est. 110 gp. m. Pressure?

If nonflowing well give depth of standing water from surface

If flowing well describe control works Installed 6" Control Valve & Ts. cemented Casing
(Type and size of valve, etc.)

Date of commencement of well Oct. 27 Date of completion of well Oct. 31.

Type of well rig Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	5	Built up Crust
8	34	16	Blue shale & gravel
34	37	3	Caprock
37	47	10	Blue lime, Boulders & Blue Mud
47	49½	2½	Hard shell
49½	67	17½	Blue shale w/ thin Rock strks.
67	79	12	Blue Shale w/ lime st.
79	82	3	Hard lime.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 37 to 47 ft.

Other aquifers

First water at 37 feet.

Casing perforated

from — to — ft.

Size of perforations

—

(OVER)