

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2630  
 Rec. 6/28 19 54  
 Well No. \_\_\_\_\_  
 Permit No. 17542  
*Do not fill in*

Owner Pat Arnold Driller Caruthers Drilling Serv  
 Address Beowawe Box 13 Address Beowawe Lic. No. 116  
 Location of well: SW 1/4 SW 1/4 Sec. 15, T. 30N/8, R. 48E, in Eureka County  
 or \_\_\_\_\_  
 Water will be used for Irrigation Total depth of well 200'  
 Size of drilled hole 14" Weight of casing per linear foot 28#  
 Thickness of casing 3/16 Temp. of water Cool  
 Diameter and length of casing Dia- 14" L-201'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface. \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well May 4th 1954 Date of completion of well May 27th 1954  
 Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Surface
2	10	8	Clay & Gravel
10	59	49	Clay
59	61	2	Sand
61	64	3	Clay
64	72	8	Sand & Water
72	80	8	Gravel--Water
80	95	15	Sandy Clay
95	98	3	Sticky Clay
98	100	2	Sand
100	108	8	Sandy Clay
108	113	5	Hard Fine Sand
113	130	17	Clay
130	142	12	Clay & Gravel
142	150	8	Sandy Clay (Soft)
150	164	<del>##</del> 14	Clay
164	170	6	Hard Sand
170	177	7	Sandy Clay & Gravel
177	187	10	Sandy Clay
187	190	3	Hard Sand
190	200	10	Clay & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 64 to 80 ft.

Other aquifers 59-61

98-100

164-170 187-190

First water at 59 feet.

Casing perforated

from 15' to 200 ft.

Size of perforations

3/16" x 1 1/2"



