Log No. 2649
Rec. 19
Well No. .....
Permit No. 15339
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

(Well plugged, replaced with attached log)

Owner: Robert J. Kost (Rainbow Apt) Driller: Effinger Bros.

Address: Tonopah Highway Address: 212 Anderson Lane Lic. No. 105

Location of well: SE ¼ NE ¼ Sec. 13, T. 20 N/S, R. 60 E, in Clark County

or .....

Water will be used for: Quasi-Municipal Total depth of well: 255 feet

Size of drilled hole: 14 Inch Weight of casing per linear foot: 24.70 lbs.

Thickness of casing: 277 Wall Temp. of water .....

Diameter and length of casing: 8 5/8"OD 255 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 42 feet from top of casing

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: May 27, 1954 Date of completion of well: June 14, 1954

Type of well rig: "71 Speed Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	Gravel
9	13	4	Cement Gravel
13	24	11	Gravel
24	33	9	Cement Gravel
33	52	19	Gravel
52	61	9	Red Sandy Clay
61	63	2	White Sand (Water)
63	65	2	Limestone
65	86	21	Sand
86	96	10	Yellow Sandy Clay
96	98	2	Limestone
98	109	11	Yellow Sandy Clay
109	118	9	Sandstone
118	125	7	Yellow Sandy Clay
125	131	6	White Clay
131	142	11	Yellow Sandy Clay
142	147	5	Limestone (Water)
147	151	4	Yellow Sandy Clay
151	156	5	Sandstone (Water)
156	185	29	Limestone
185	192	7	Cement Gravel
192	195	3	Gravel
195	201	6	Cement Gravel
201	203	2	Red Sticky Clay
203	255	52	Gravel (Water)

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 203 to 255 ft.

Other aquifers: 151-156, 142-147

First water at 61 feet.

Casing perforated

from 100 to 255 ft.

Size of perforations

1/8" X 12"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8"OD	0	255	255	Cemented from 0 to 40 feet Graveled packed from 40 to 255 feet 7 yards of pea gravel 1½ yards of concrete

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.
Well Driller

By A. T. Effinger

License No. 105

Date June 14, 1954, 19

(Not to be filled in by Driller)