WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2676
Rec. Aug 30 1954
Well No.
Permit No.
Do not fill in

Owner Art Downs Driller Fred Erb

Address Fallon Nev. Address East Star Route Fallon Nev. Lic. No. 121

Location of well: NE ¼ SE ¼ Sec. 29, T. 19 N/~~S~~, R. 28 E, in Churchill County

or

Water will be used for Domestic Total depth of well 24 feet.

Size of drilled hole 6 inch Weight of casing per linear foot

Thickness of casing 20 gauge Galvinized Temp. of water 62°

Diameter and length of casing 6 inch Casing 24 ft long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 feet.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well July 22, 1954 Date of completion of well July 28, 1954,

Type of well rig Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Black Loam
2	8	6	fine Sand
8	9	1	adobie
9	14	5	fine Sand
14	20	6	Brown Sand
20	24	4	Gravel.

Water-bearing Formation, Casing Perforations, Etc.
Gravel

Chief aquifer (water-bearing formation)
from 20 to 24 ft.

Other aquifers Sand

First water at 9 feet.

Casing perforated
from 16 to 24 ft.

Size of perforations
1 in X 1/64 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in	0	24	24	20 gauge Galvanized Casing and Screened Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pumping test about 800 gal. per hour.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs Fred Erb

License No.

Dated Aug 16, 1954

(Not to be filled in by Driller)