

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 2695
 Rec. Aug 16 19 54
 Well No. _____
 Permit No. _____

Do not fill in

Owner J. WHEELER Driller Bob MEYER
 Address CARSON CITY Address CARSON CITY Lic. No. 10
 Location of well: SE SE 1/4 Sec. 10, T. 15 N/S, R. 18 E, in ORMSBY County
 or 7 miles W side of Lake Toiyabe
 Water will be used for DOMESTIC Total depth of well 150'
 Size of drilled hole 6" Weight of casing per linear foot 13 LBS'
 Thickness of casing 3/16 Temp. of water COOL
 Diameter and length of casing 6" — 150'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure NO
 If nonflowing well give depth of standing water from surface 18'
 If flowing well describe control works NO
 (Type and size of valve, etc.)
 Date of commencement of well July 9 Date of completion of well July 20 54
 Type of well rig CRANK TOOLS

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	ROCK CLAY.
5	40	35	SANDY CLAY.
40	45	5	SAND-WATER.
45	80	35	SANDY CLAY.
80	90	10	ROCK-CLAY.
90	120	30	SANDY CLAY.
120	150	30	ROCK. CLAY.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 40 to 45 ft.

Other aquifers _____

First water at 40 feet.

Casing perforated

from 130 to 150 ft.

Size of perforations

1 1/2"



