

PROBABLE  
APN

37-330-08

PORTION — NE<sup>4</sup> SE<sup>4</sup> SECTION 02

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2722  
Rec. Sept. 15 1954  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
*Do not fill in*

Owner James Tucker Driller Mel Meyer Co. Lee Smith

Address Prater Way & Vista Rd. Sparks, Nevada Address 190 Moapa Lane - Reno, Nev. Lic. No. 3

Location of well: SE 02 dabc / NE 1/4 NE 1/4 Sec. 12, T.19 N/8, R. 20 E, in Washoe County

Water will be used for Domestic use Total depth of well 150'

Size of drilled hole 6" Weight of casing per linear foot 10 1/2 lbs

Thickness of casing 5/16" Temp. of water cold

Diameter and length of casing 6" ID x 155'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 52'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well September 2, 1954 Date of completion of well September 11, 1954

Type of well rig Cable tool

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	clay - boulders
30	50	20	sandy clay
30	55	5	sandy clay
55	60	5	sandy clay
60	95	35	quick sand
95	129	34	sand - some water
129	165	36	clay - gravel
165	180	15	clay - gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 129 to 160 ft.

Other aquifers \_\_\_\_\_

First water at 129 feet.

Casing perforated

from 42' to 62' ft.

Size of perforations

5/16" x 6"



