Hist. Log 2700

2723

Log No. 2723
Rec. 9/9/54 19 54
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner: Primm Investment Co Driller: Roscoe Moss

Address: Gardena, Calif. Address: 4360 No. Worth St. L.A. Calif. Lic. No. 8

Location of well: ____¼____¼ Sec. 5, T. approx 32 N/S, R. 64 E, in Clark County

or

Water will be used for ____ Total depth of well ____

Size of drilled hole 18" Weight of casing per linear foot ____

Thickness of casing 3/16" Temp. of water ____

Diameter and length of casing 16" I.D. & 12 3/4 OD.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure ____

If nonflowing well give depth of standing water from surface ____

If flowing well describe control works ____
(Type and size of valve, etc.)

Date of commencement of well June 24, 1954 Date of completion of well Aug. 3, 1954

Type of well rig ____

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
671	700	29.	Partially decomposed granite.
700	740	40	Sandy yellow Clay & Granite Rock
740	748	8	Sand & Gravel to 6" some Clay.
			12" Casing was collapsed from 552' to 660'. Started swedging with 8" swedge and increased to size 12". Went outside pipe of 615', drilling up and passed bottom 46', drilled to 748 ft. pulled out 12" Casing. Water raised 5' when well was bailed with Scow.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from ____ to ____ ft.

Other aquifers ____

First water at 103 feet.

Casing perforated

from ____ to ____ ft.

Size of perforations ____

919