

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2725
 Rec. Sept. 15 1954
 Well No.
 Permit No.
Do not fill in

Owner W. W. Clyde Constr. Co. Driller J. D. Hill
 Address Springville, Utah Address Ely, Nevada Lic. No. 14
 Location of well: $\frac{1}{4}$ Sec. 13, T. 17 N. 8 E, R. 6 E, in White Pine County
 or 15 miles west of Ely on south side of Highway 50
 Water will be used for road construction Total depth of well 375 feet
 Size of drilled hole 6" Weight of casing per linear foot 20#
 Thickness of casing $\frac{1}{4}$ " Temp. of water
 Diameter and length of casing 6" x 335'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 280 feet
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well July 15, 1954 Date of completion of well Aug. 15, 1954
 Type of well rig Churn drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5	5	Soil	
5	295	290	Cemented gravel	
295	300	5	Sand and gravel	Chief aquifer (water-bearing formation) from <u>295</u> to <u>300</u> ft.
300	375	75	Cemented gravel	Other aquifers <u> </u>
				First water at <u>295</u> feet.
				Casing perforated from <u>260</u> to <u>335</u> ft.
				Size of perforations <u>$\frac{1}{2}$ x 6</u>

(OVER)

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT


This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. O. Hill
Well Driller

By.....

License No. 17

Dated 9-12, 1954



(Not to be filled in by Driller)
