WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2726
Rec. Sept 20 54
Well No. 9 5
Permit No. 1-7703 / 1-399
Do not fill in U/

Owner: Stardust, Inc.

Driller: J. R. Kelsen H. E. Miller Long Beach

Address: Hwy 91 On The Strip Las Vegas, Nevada

Address: 3035 Cherry Ave/ Calif

Lic. No. 178

Location of well: NE 1/4 SE 1/4 Sec. 9, T. 21 S, R 61 E, in Clark County

or

Water will be used for

Total depth of well 801'

Size of drilled hole 17½"

Weight of casing per linear foot 30# 22#

Thickness of casing ¼"

Temp. of water 78°

Diameter and length of casing 8¼" and 10¼"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Before pumping well flowed 6 0 gm

If nonflowing well give depth of standing water from surface Water at surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well June 3, 1954

Date of completion of well September 1, 1954

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	24	24	Gitche Colicha
24	34	10	Loose contaminated gravel
34	68	34	Boulders
68	80	12	Gravel w/Red Clay
80	82	2	Hard shell
82	97	15	Water gravel fine well washed w/Red and Gray gravel
97	330	233	Red sticky clay w/some fine gravel
330	362	32	Water gravel w/fine white sand
362	385	23	Shells (lime) (acid cut)
385	455	70	Red clay (sticky)
455	458	3	Shell
458	470	12	Bentonite or Blue clay
470	544	74	White clay Bentonite
544	560	16	Shells
560	585	25	Gravel fine
585	590	5	Shell
590	795	205	Red sand w/ltd2' streaks of clay
795	801	6	Hard formation No sampler

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 82 to 97 ft

Other aquifers 330-362

595 to 795

First water at 82 feet

Casing perforated

from 601 to 801 ft

Size of perforations

100 mesh

(OVER)

LOG OF FORMATIONS

From feet	To feet	Thickness	Type

CASING RECORD

Diameter	From feet	To feet	Length	Remarks (Seals, Grouting, Etc.)
1[illegible]" ID	0	26'	26	Conductor
10 3/4 ID	0	601	601	Cemented from 544 to 440
8 5/8 ID	601	801	200	Cemented from 130 to 20' w/100 mesh perfs.

GENERAL INFORMATION (Pumping Test, Quality of Water, Etc.)

On pumping test Well pumped at rate of 360 to 400 G pm.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed: [illegible]
Well Driller

By

License No. [illegible]

(Not to be filled in by Driller)