WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2738
Rec. Oct. 7 1954
Well No.
Permit No.
Do not fill in

Owner Leonard Hopkins Driller J. R. Reynolds
Address Wells Nev Address Fallon Nev Lic. No. 28
Location of well: ¼ SW ¼ Sec. 3, T. 38 N/S, R. 63 E, in Elko County
or
Water will be used for irrigation & stock Total depth of well
Size of drilled hole 6" six inch Weight of casing per linear foot 12 lbs per ft
Thickness of casing 5/16" approx Temp. of water
Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 30' Thirty.
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well Aug 16/54 Date of completion of well Aug 17/54
Type of well rig Cable tools Star 71

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Silt soil & Gravel.
40	45	5	Clay & gravel
45	51	6	~~Gravel~~ Brown clay
51	55	4	Brown clay
55	62	7	Pea sized gravel & water sand.
62	67	5	Brown clay
67	77	11	Gravel & water,
77	81	4	Brown clay
81	104	23	Gravel & water bearing.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 81 to 104 ft.
Other aquifers all of these gravel strata have water.

First water at 30 feet.

Casing perforated
from 30 to 102 ft.

Size of perforations
4" x 3"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

well test well in the spring of 55
Bailed 50 G.P.M. 30 MINUTE TEST.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J.B. Reynolds
Well Driller

By.....

License No. 28

Dated 1-7-16, 19 56

(Not to be filled in by Driller)