

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2743
 Rec. Oct. 13 1957
 Well No.
 Permit No.

Do not fill in

Owner U.S. Bureau of Land Management Driller Hel Meyer Company

Address 1061 W. Highland Blvd. Portland, O. Ore. Address 190 Cassa Lane - Reno Lic. No. 3

Location of well: SW 1/4 1/4 Sec. 15, T. 40. N. 8, R. 20 E, in Washoe County

or Business Well

Water will be used for Domestic Total depth of well 234'

Size of drilled hole 6" Weight of casing per linear foot 12 7/8 per

Thickness of casing 2/16" Temp. of water 60.5

Diameter and length of casing 5 1/2' x 11' or 234'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 100'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 10/1/57 Date of completion of well 10/8/57

Type of well rig Artisanal

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Boulders & clay - red
15	45	30	Sandy clay - brown
45	73	28	Sandy clay - white
73	100	27	Coarse sand & clay - brown
100	135	35	" " " "
135	187	52	Unconsolidated gravel & water
187	234	47	Broken rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 105 to 234 ft.

Other aquifers.....

First water at 105 feet.

Casing perforated

from 102 to 232 ft.

Size of perforations

2/16" x 6"



