

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 2786
 Rec. Dec. 3 1954
 Well No. _____
 Permit No. _____

Do not fill in

Owner Raymond Avinsino Driller J. C. Faretto & Son
 Address 1040 Lander St, Reno, Nev. Address 736 Humboldt St, Reno Lic. No. 2
 Location of well: SW 1/4 NE 1/4 Sec. 1, T.18. N. 8, R. 19. E, in Truckee Meadows, Washoe County
 or 1 mile west from Reno-Carson Hwy. on Huffacker Lane turn north on Davis Lane.
 Water will be used for Domestic Total depth of well 87'-02"
 Size of drilled hole 6 inch Weight of casing per linear foot 12.89 Lbs.
 Thickness of casing .188 of an inch Temp. of water 58°
 Diameter and length of casing Diam. O.D. 6 5/8", 9'-04" to 10'-00" lengths
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 18'-09"
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well Nov 12, 1954 Date of completion of well Nov 22, 1954
 Type of well rig Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	26	26	Yellow clay with coarse sand & gravel.
26	39	13	1st water. Water level 22'-06". Little water. Yellow clay with coarse sand & gravel. Stony. Looset Soft.
39	50	11	2nd water. Little water. Yellow clay with fine to coarse sand & gravel, stony.
50	60	10	No water. Yellow clay. Sticky, hard.
60	75	15	3rd water. Water level 29'-00". Very little water. Yellow clay with a little fine to coarse sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 90 to 95 ft.

Other aquifers 85 to 90
75 to 80

First water at 26 feet.

Casing perforated from 75 to 85 ft.

Size of perforations 3/8" x 1"



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
75	80	5	6 gravel, Soft & sticky. 4th water, Water level 25'-08". Little water. Clay with medium to coarse sand & gravel.
80	85	5	Yellow clay. Water level 36'-00".
85	90	5	5th water, Water level 26'-10". Little water. Yellow clay with medium to coarse sand & gravel. Rocky.
90	95	5	6th water, Yellow clay with medium to coarse sand & gravel. Rocky.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0'-06"	86'-08"	87'-02"	Substandard pipe, Welded with 4"x3" steel couplings, Short pattern shot, Perforated with Mills perforator.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Clay formation. Sand material brown, light & black, mostly brown material, Gravel sharp & angular, some smooth & worn. Well cleaned & tested with compressor 5'-05" draw-down pumping 11 gal. per minute.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J.C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated November 27, 1954

(Not to be filled in by Driller)

