

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2848
 Rec. Mar. 1 1956
 Well No.
 Permit No.
Do not fill in

Owner Mr. C. L. Crawford Driller Frank W. Parks
 Address Silver Springs, Nev. Address Box 202 Fernley, Nev. Lic. No. 139
 Location of well: 1/4 Sec. 30., T. 13 N/S, R. 24 E, in Lyon County
 or about 3 1/2 mi. SE of Silver Springs Post Office
 Water will be used for Domestic Total depth of well 120 ft.
 Size of drilled hole 6 inch Weight of casing per linear foot
 Thickness of casing 3/32 Temp. of water about 64 deg. when pumped
 Diameter and length of casing 6 in. dia. length 120 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 30 ft. when cased
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well Sept. 6th 54 Date of completion of well Feb. 1st. 55
 Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	21	21	sand
21	25	4	sand & clay, hard
25	30	5	sand & gravel, some water
30	38	8	clay & sand, hard
38	41	3	sand & gravel
41	44	3	soft gray clay
44 to	50	6	sand & clay, hard
50	70	20	sand, clay & gravel, hard
70	94	24	soft blue clay, some water
94	108	14	blue clay, mica specks
108	112	4	blue clay, hard
112	118	6	water bearing gravel
118	120	2	boulders & water bearing gravel. bottom of hole

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 112 to 120 ft.

Other aquifers

gravel & blue clay

First water at 30 feet.

Casing perforated

from 108 to 120 ft.

Size of perforations

3/16 by 2 in.

