

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA


Log No. 2861

Rec. Jan 31 1955

Well No. _____

Permit No. _____

Do not fill in



Owner Primm Investment Company Driller Roscoe Moss Company

Address Gardena, California Address 4360 Worth Street Lic. No. 8

Location of well: N.E. 1/4, N.E. 1/4 Sec. 16, T.27. N/S, R. 57 E, in Clark County
of Bordertown, Nevada

Water will be used for Domestic Total depth of well 555

Size of drilled hole 14 Weight of casing per linear foot 25.16

Thickness of casing 3/16" Temp. of water 68°

Diameter and length of casing 12-3/4" O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not flowing

If nonflowing well give depth of standing water from surface 105

If flowing well describe control works Not flowing
(Type and size of valve, etc.)

Date of commencement of well October 26, 1954 Date of completion of well January 5, 1955

Type of well rig Calif. Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8		Brown clay
8	28		Caliche
28	158		Caliche and gravel
158	270		Brown clay and gravel
270	273		Red clay
273	300		Sticky brown clay and some gravel
300	392		Brown clay and gravel
392	498		Brown clay and broken rock
498	555		Volcanic rock

Water-bearing Formation, Casing
Perforations, Etc.

Chief aquifer (water-bearing
formation)

from _____ to _____ ft.

Other aquifers _____

First water at 130 feet.

(Casing perforated

from Not Perforated. ft.

Size of perforations _____

