WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2888
Rec. April 5 1955
Well No.
Permit No. 14799
Do not fill in

Owner Anthony J Carrado Jack D. Roaklidge Driller Don Miller

Address Irona Calif Address Pahrump Lic. No. 129

Location of well: NW ¼ SE ¼ Sec. 6, T. 20 N/S, R 53 E, in Nye County

or

Water will be used for Irrigation Total depth of well 200 ft

Size of drilled hole 15 1/2 Weight of casing per linear foot 10 gage

Thickness of casing 3/16 Temp. of water

Diameter and length of casing 200 ft 14" O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 17 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 3/10-55 Date of completion of well 3/20-55

Type of well rig 72 Star Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Clay & Colichia
18	25		Water sand
25	40		Clay
40	50		Water sand
50	80		Clay
80	92		Water sand
92	165		Clay
165	175		Water sand
175	180		Blue Clay
180	190		Clay
190	200		Water sand

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 18 to 25 ft.

Other aquifers 40-50
80-92
165-175
190-200

First water at 18 feet.

Casing perforated

from 18-25 to 40-50 ft.
165-175 - 190-200

Size of perforations

1/4 x 3

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14" O.D.	0	200	200	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Tom Miller
Well Driller

By

License No. 12

Dated March 31, 1955

OFFICE
STATE ENGINEER
APR - 5 55
RECEIVED
ANS.

(Not to be filled in by Driller)