

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Bureau Of Land Management

Log No. 2991
 Rec. June 5 19 55
 Well No.
 Permit No.
Do not fill in

Owner W. T. Jenkins Co Driller Carruthers Drilling Service
 Address Battle Mountain Address Beowawe Lic. No. 116
 Location of well: SW 1/4 1/4 Sec. 14, T. 36 N, R. 44 E, in Lander Co County
 or
 Water will be used for Stock Total depth of well 200 FT
 Size of drilled hole 6" Weight of casing per linear foot Standard
 Thickness of casing 3/8 Temp. of water
 Diameter and length of casing 6" 1 D-24 FT Long
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well April 9th 1955 Date of completion of well May 3rd 1955
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Surface
4	10	6	Sand Gravel
10	14	4	Boulders
14	16	2	Decomposed Granite
16	20	4	Sand
20	23	3	Rock (Boulder)
23	25	2	Sand
25	49	24	Decomposed Granite (Soft)
49	53	4	Rock (Boulder)
53	65	12	Decomposed Granite
65	80	15	Sandy Clay & Sand Streaks
80	92	12	Decomposed Granite
92	110	18	Sandy Clay & Sand
110	117	7	Clay
117	133	16	Sandy Clay & Sand Streaks
133	152	19	Decomposed Granite (Soft)
152	156	4	Clay
156	160	4	Sand
160	172	12	Clay
172	200	28	Silty Sand (Soft)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers.....

First water at feet.

Casing perforated
 from 98 to 170 ft.

Size of perforations

1/8 x 12" Slots



