

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 3007
 Rec. June 15 1955
 Well No.
 Permit No.

Do not fill in

Owner LEO. SPURER Driller HARVEY MEYER
 Address WASHOE VALLEY Address CARSON CITY Lic. No. 10
 Location of well: SW SW $\frac{1}{4}$ Sec. 12 T. 12 N. $\frac{1}{2}$, R. 19 E, in WASHOE County
 or Placer

Water will be used for..... Total depth of well 150'
 Size of drilled hole 12" - 10" Weight of casing per linear foot 32 lbs.
 Thickness of casing 1/4" Temp. of water Cool
 Diameter and length of casing 10" - 132'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure no
 If nonflowing well give depth of standing water from surface 90'
 If flowing well describe control works no
 (Type and size of valve, etc.)

Date of commencement of well APR. 20 Date of completion of well MAY 11th
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5	5	Rock - SAND.	
5	35	30	Rock CLAY.	Chief aquifer (water-bearing formation) from <u>35'</u> to <u>150'</u> ft.
35	40	5	Rock.	Other aquifers.....
40	102	62	Rock - CLAY.	
102	180	8	Rock - SAND WATER.	
110	150	40	Rock SANDY CLAY.	
				First water at <u>5'</u> feet.
				Casing perforated from <u>30'</u> to <u>150'</u> ft.
				Size of perforations <u>3/16</u>



