WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3094
Rec. Aug. 23 1955
Well No.
Permit No.
Do not fill in

Owner: L. G. Cox
Driller: Fred Esh
Address: Schurz, Nevada
Address: 6 Star Rt. Fallon, Nevada
Lic. No. 121

Location of well: W½SW¼NW¼ Sec. 9, T. 12 N/S, R 29 E, in Mineral County

or

Water will be used for: Domestic
Total depth of well: 42 feet

Size of drilled hole: 6 inch
Weight of casing per linear foot:

Thickness of casing: 20 gauge Galvanized
Temp. of water: 61°

Diameter and length of casing: 6 inch Casing 42 feet long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 30 feet

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: July 28-55
Date of completion of well: July 31, 1955

Type of well rig: Cable Tool Well Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sand
8	9	1	adobie
9	21	12	Sand
21	22	1	Gravel
22	27	5	Sand
27	28	1	adobie
28	33	5	Sand
33	34	1	Gravel
34	37	3	Sand
37	42	5	Gravel

Water-bearing Formation, Casing Perforations, Etc.
Gravel

Chief aquifer (water-bearing formation)
from 37 to 42 ft.

Other aquifers

First water at 21 feet.

Casing perforated
from 32 to 42 ft.

Size of perforations
1/64 x 1 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 in.	0	42	42 ft	20 gauge Galvinized Casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 800 gal per Hour.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs Fred Erb

License No. 121

Dated Aug 2, 1955

OFFICE
STATE ENGINEER

(Not to be filled in by Driller)

1955 AUG 23 AM 9 33