WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3117
Rec. Aug. 29. 1955
Well No.
Permit No.
Do not fill in

Owner OLIVER M ROUSSEAU Driller CHANDA DRILLING CO.

Address 1373 JACKSON ST. HAYWARD CALIF. Address KINGS BEACH, CALIF. Lic. No. 85

Location of well: LOT ~~1/4 1/4~~ Sec. 22, T. 16 N/~~S~~, R. 18 E, in WASHOE County

or

Water will be used for DOMESTIC Total depth of well 152 FT.

Size of drilled hole 8" Weight of casing per linear foot

Thickness of casing 10 GA. Temp. of water COLD

Diameter and length of casing 8" DIA 152 FT LONG
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure ——

If nonflowing well give depth of standing water from surface 34 FT.

If flowing well describe control works ——
(Type and size of valve, etc.)

Date of commencement of well 7/16/55 Date of completion of well 7/30/55

Type of well rig CABLE

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	38	38	SAND & CLAY PACKED
38	91	53	LOOSE WATER BEARING SAND.
91	103	12	CLAY & SAND (LOOSE, MUCKY)
103	132	29	LOOSE SAND & WATER
132	136	4	HARD LAYER OF D.G.
136	152	26	LOOSE WATER BEARING SAND

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 136 to 152 ft.

Other aquifers
38 – 91
103 – 132

First water at 38 feet.

Casing perforated
from 125 to 150 ft.

Size of perforations
1/4" X 1 1/4"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	152	152	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

COMPRESSOR JET PUMPED, GOOD WATER, 2,500 G/HR -18 FT DRAW DOWN

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed L. H. Clenda
Well Driller

By.....

License No. 86

Dated 8/15/55, 194.

OFFICE
STATE ENGINEER

1955 AUG 29 AM 8 06

(Not to be filled in by Driller)